

Docket No.: APPL-P2840

RESPONSE**IN THE CLAIMS:**

What is claimed is

1. (Once amended) In a serial bus module having a plurality of link devices, a method for presenting the plurality of link devices as separate nodes comprising:
- a) creating an individual configuration ROM image for each link device in said plurality; and
 - b) presenting said configuration ROM images for each said link device.
2. (Once amended) The method of claim 1 wherein each said configuration ROM image includes an entry for a distinct identifier for a corresponding link device.
3. (Original) The method of claim 2 wherein said presenting said configuration ROM image comprises:
- a) receiving from one of said link devices a block request and a link ID; and
 - b) providing configuration ROM associated with said link ID.
4. (Once amended) The method of claim 1 wherein said creating and presenting said configuration ROM image are carried out by transaction layer software.
5. (Original) A serial bus module device comprising:
- a) a plurality of link layer devices;
 - b) a transaction layer software; and

Docket No.: APPL-P2840

- c) for each of said link layer device, a distinct configuration ROM image presented by said transaction layer software.
6. (Original) The serial bus module device of claim 5, wherein each said link layer device includes an associated global unique identifier, and wherein each said configuration ROM image includes a corresponding entry for said associated global unique identifier.
7. (Once amended) A communication system comprising:
- a) a plurality of serial bus modules; and
 - b) a serial bus connected to each said serial bus modules, at least one of said modules comprising a plurality of link layer devices, a transaction layer software, and for each of said link layer device, a distinct configuration ROM image presented by said transaction layer software.
8. (Original) The communication system of claim 7, wherein each said link layer device includes an associated global unique identifier, and wherein each said configuration ROM image includes a corresponding entry for said associated global unique identifier.
9. (Once amended) A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method for presenting a plurality link devices in a single device as separate nodes said method comprising:
- a) creating an individual configuration ROM image for each link device; and
 - b) presenting said configuration ROM image for each said link device.

Docket No.: APPL.-P2840

10. (Original) The program storage device of claim 9 wherein each said configuration ROM image includes a entry for a distinct identifier for a corresponding link device.

11. (Original) The program storage device of claim 10 wherein said presenting said configuration ROM image comprises:

- a) receiving from one of said link devices a block request and a link ID; and
 - b) providing configuration ROM associated with said link ID.
-